

# Xintekvideo INC.

## SDI COLOR CORRECTOR MODEL HD-900M



### DESCRIPTION:

Xintekvideo's Model HD-900M is an all digital Color Corrector that directly interfaces with HD digital video and provides the means to color match any video clip to a wanted color standard. It is most often used to match video to any display characteristics.

The Model HD-900M provides a wide-range control of amplitude and pedestal for each primary color, permitting full balance of highlights as well as low lights. In addition it has controls for Chroma Gain, Brightness, and Gamma Correction.

The Model HD-900M permits storing into memory 12 correction pre-sets. Up to 400 pre-sets are optionally available. Any stored preset can be recalled and used to control the video processing. It can also be modified, using the front panel controls, and re-saved into its memory or into a different memory. Optional remote control is available via the USB port of any PC.

The most appreciated feature of the Model HD-900M is its ease of operation due to its individual, simultaneously operable, independent front panel controls for each function. No need to go through menus and search for the desired function. That makes the system extremely user's friendly. Color correction is normally an iterative process in which 6 to 9 different functions may need to be adjusted interactively. The HD-900M provides simultaneous access to all of those functions!

The Model HD-900M will not affect embedded signals in the video stream as it automatically goes into process bypass during non video time.

### SPECIFICATIONS:

Input: 4:2:2 Serial Digital video at 1.485 Gbs  
Optional Standard Video 270 Mbs operation  
Unprocessed Output: Equalized and re-clocked input  
Optional Input: Analog Component or Composite Video  
Processed Output: Two digital video outputs at 1.485 Gbs  
(Optional 270 Mbs operation)  
Optional Output: Analog Component or Composite Video  
Optional Remote Control via the USB port of any PC  
Processing Accuracy: 10 to 12 bit processing accuracy  
CONTROL FUNCTIONS: Red Gain:  $\pm 40\%$   
Red Pedestal:  $\pm 25$  IRE  
Blue Gain:  $\pm 40\%$   
Blue Pedestal:  $\pm 25$  IRE  
Green Gain:  $\pm 40\%$   
Green Pedestal:  $\pm 20$  IRE  
Chroma Gain:  $\pm 50\%$   
Y set-up:  $\pm 12$  IRE  
Y Gamma: .3, .5, .8, 1.0, 1.3, 1.5, 1.8  
Process/Bypass switch  
Front Panel or Pre-Set Selection  
Pre-set memory selection  
Store into memory control  
System Delay: 200 nsec. nominal  
Power Requirement: 100-240v AC, 50/ 60 Hz, 10 Watts  
Operating Temperature: 32<sup>o</sup> F to 110<sup>o</sup> F, ambient  
Humidity: 10% to 90% non-condensing  
Mechanical: 1RU cabinet: 1.75"H, 19"W, 10"L; 6Lbs

Specifications subject to change without notice. 07/2008

**XINTEKVIDEO INC**  
56 West Broad Street  
Stamford, CT 06902

(203) 348-9229

[www.xintekvideo.com](http://www.xintekvideo.com)